

DIGITAL AIR FLOW ANEMOMETER MODEL NO.BE856



APPLICATION

This multifunction anemometer provides instant data such as Air Speed ,Temperature and Air flow(CMM) in triple Level LCD display with Backlight. This tool has wide measuring range of wind speed from 0~ 45m/s (0 ~ 8800ft/min),temperature from 0 ~ 45°C (32 ~ 113°F) and air flow(CMM) measuring range 0~999900m³/min, with USB Interface to computer .This weather device is an ideal tool for windsurfing, sailing and kite flying. You can also use it for industrial and home purposes such as measuring speed and temperature of CPU computer fans, air-conditioners, airflow over the roof or walls .All-in-one design makes you enjoy your measurement in the field of environment protection marine operation aviation, industry and agriculture with real output.

KEY FEATURES

- Simultaneous measure and display Air Velocity, Temperature, Air flow.
- Digital Thermometer with range 0 ~ 45 °C (32 ~ 113 °F)
- Fast Air velocity measure range: 0.3 ~ 45 m/s (0 ~ 8800 ft/min)
- Air flow measuring range(CMM):0~999900m³/min
- Multiple SI units: m/s, km/h, ft/min, mph ,knots,m³/min(cmm)
- Wind velocity is also displayed in a Beaufort wind scale bar graph
- Display options in wind speed mode are current wind speed, maximum and minimum wind speed and average wind speed
- Special Functions
Wind Speed/Velocity: Current (Cu), Maximum (MAX), Minimum (MIN) and Average (AVG)
Backlight
- Guaranteed quick response & accurate readings, no guessing errors
- Wind chill is displayed in the selected temperature unit
- Switchable between °C or °F
- Separate rotating vane sensor and Backlight
- Auto/Manual power-off with low battery warning
- Measurement units & parameters
Air Speed/Velocity: m/s, km/h, ft/min, knots, mph
Air Temperature: °C & °F
Air Flow:m³/min
- NTC Thermometer
- USB Interface
- Data hold function



DIGITAL AIR FLOW ANEMOMETER MODEL NO.BE856

SPECIFICATIONS

- * Digital Thermometer with range 0.3-45 °C (32 -113 °F);Accuracy:±2°C
- * Fast Air Velocity measure range: 0.3-45 m/s (0 -8800 ft/min);0-140km/hr;0-8800ft/min;0-88knots;0-100mph
- * Air velocity measuring Accuracy:±3%±0.1dgts
- * Air flow measuring range:0~999900m³/min
- * Resolution: 0.1m/s,0.2°C
- * Multiple SI units: m/s, km/h, ft/min, mph or knots,m³/min
- * °F or °C Selection
- * Wind Chill measuring
- * LCD Backlight display
- * Max/min reading
- * Average/Current reading
- * Data hold
- * Low battery indication
- * Manual/Auto power off
- * USB interface
- * Unit size: 77 x36 x163.5mm
- * Power: 1.5V AAA batteries x 4pcs



ACCESSORIES

- * Sensor Vane Probe (connected to main unit) x 1pc
- * Protective Rubber Back Cover x 1 pc
- * 1.5V AAA battery x 4pcs
- * USB connect cable and software x 1 set
- * Manual x 1 pc
- * gift box and carrying case

BESTONE INDUSTRIAL LTD.

Tel: +86 755 82952326, Fax: +86 755 82952326

Web: www.bestone-meter.com

Email: liu@bestone-meter.com

Skype: Bestone-Shirley Liu

WhatsApp: +86 18929394326