

**DIGITAL ANEMOMETER WITH SOFTWARE**  
**MODEL NO.EAM03**

**APPLICATION**

This multifunction anemometer provides instant data such as Air Speed and Temperature, Humidity and Air flow in multiple Level LCD display with Backlight. This tool has wide measuring range of wind speed from 0.8~ 30m/s and temperature from -20 ~ 60°C and Air Relative Humidity:0 to 100% RH,CFM:0 to 99990 This weather device is an ideal tool for windsurfing, sailing and kite flying. You can also use it for industrial and home purposes such as measuring speed and temperature of CPU computer fans, air-conditioners, airflow over the roof or walls



**KEY FEATURES**

- Simultaneous display of air flow or Air velocity plus ambient temperature and relative humidity
- Easy to set area dimensions are stored in the meter's internal memory for the next power on
- Resolution of 0.01 m/sec
- 20 points average for air flow
- Super large(9999 counts) LCD backlight display
- Max/min hold and display hold function
- Dual display (plus T&TH)
- Backlight function
- Auto power off
- Temperature scale switch: °C/°F
- Overflow indication: "OL" will be show in LCD
- Low battery voltage indication
- USB interface& PC-Software.



高度/Height : 165mm  
宽度/Width : 85mm  
厚度/Thickness : 38mm  
重量/Weight : 200g

## DIGITAL ANEMOMETER WITH SOFTWARE MODEL NO. EAM03

### SPECIFICATIONS

- \* Air Velocity Range:  
m/s(meter per second):0.80~30.0, Accuracy:±(2.0% reading + 50)  
Ft/m(feet per minute):78~5900,Accuracy:±(2.0% reading +50)  
Km/h(kilometer per hour):1.4~108.0,Km/h ,Accuracy:±(2.0% reading + 50)  
Mile/h(mile per hour):0.9~67.0,Accuracy:±(2.0% reading + 50)  
Knots(nautical miles per hour):0.8~58.0,Accuracy:±(2.0% reading + 50)  
Ft/s(feet per second):1.3~98.5,accuracy:±(2.0% reading + 50)
- \* Air temperature:-20 to 60°C(-14 to 140°F),Accuracy:1.5°C(±2.7°F)
- \* Air Relative Humidity:0 to 100% RH ,Accuracy:±3%
- \* Air Flow Range  
CFM:0 to 99990, Area:0 to 9.999ft<sup>2</sup>  
CMM:0 to 99990, Area:0 to 9.999ft<sup>2</sup>  
CMS:0 to 9999,0 to 9.999ft<sup>2</sup>
- \* Flow Area Setting
- \* MAX/MIN Function
- \* Display backlight
- \* Auto Power off
- \* Low battery indication
- \* °C/°F Selection
- \* Ambient ,Dew point& wet bulb temperature selection
- \* USB Interface ,USB Cable ,WIN PC-software
- \* Power supply:1x9V 6F 22
- \* Product Size:168mmx85mmx43mm(6.5"x3.3"x1.5")
- \* Product weight:200g(0.41b)
- \* Category: CE



### ACCESSORIES

- \* 1 x Carrying Pouch
- \* 1 x 9V battery
- \* 1 x USB connect cable and Software
- \* 1 x Manual
- \* Standard factory packing

## **BESTONE INDUSTRIAL LTD.**

Tel: +86 755 82952326, Fax: +86 755 82952326

Web: [www.bestone-meter.com](http://www.bestone-meter.com)

Email: [liu@bestone-meter.com](mailto:liu@bestone-meter.com)

Skype: Bestone-Shirley Liu

WhatsApp: +86 18929394326