

Ultrasonic Thickness Meter
MODEL NO. TM-8816/TM-8816C/TM-8818



TM-8818



TM-8816/
TM-8816C



Ultrasonic Probe

APPLICATION

Used for measuring thickness and corrosion of pressure vessels, chemical equipment, boilers, oil storage tanks, etc. in industries of petroleum, shipbuilding, power station, and machine manufacturing. Applicable to measure the thickness of many materials, e.g. Steel, Cast iron, Aluminum, Red copper, Brass, Zinc, Quartz glass, Polyethylene, PVC, Gray cast iron, Nodular cast iron

KEY FEATURES

- ✓ With high power of emission and broad band of receiving sensitivity, the gauge can match probes of different frequencies. That makes it easy to measure the rough surface, even cast iron. It is widely used in almost all kinds of industries.
- ✓ The model TM-8818 has bidirectional measurements, materials thickness is measurable with know velocity, conversely velocity is measurable with know thickness.
- ✓ Automatic memory material code and sound velocity value, convenient to use.
- ✓ Coupling symbol indication when measuring.
- ✓ Manual or automatic power off.
- ✓ Applies USB, RS-232, Bluetooth data output.

Material Selection

Code Material

Cd01: Steel
cd02: Cast Iron
cd03 :Aluminum
cd04: Red Copper
cd05 :Brass
cd06: Zinc
cd07:Quartz Glass

Code Material

cd08: Polyethylene
cd09: PVC
cd10: Gray Cast Iron
cd11: Nodular Cast Iron
xxxx: Sound Velocity

Ultrasonic Thickness Meter

MODEL NO. TM-8816/TM-8816C/TM-8818







SPECIFICATIONS

Model	TM-8818	TM-8816	TM-8816C
Housing Material	Aluminum Alloy	Strong, Light Weight ABS-Plastic	
Display	Large Screen LCD	4 Digit, 10 mm LCD	
Measuring Range	0.75~400 mm (45 # steel, Depend on Probe)	1.0~200 mm / 0.04~8 inch	
Resolution	0.01 mm / 0.1 mm / 0.001 inch	0.1 mm	0.01 mm
Accuracy	$\pm (0.5\%n + 0.05)$		
Sound Velocity	500~9,990 m/s		
Lower Limit of Pipes	$\Phi 15 \times 2.0 \text{ mm } \Phi 20 \times 3.0 \text{ mm}$ Determined By Transducer		
Operating Temperature	0~40°C		
Conditions Humidity	< 85%RH		
Power Supply	2x1.5V AA (UM-3) Battery	4x1.5V AAA (UM-4) Battery	
Dimensions	130x76x32mm	135x65x27mm	
Weight	340g (Not Including Batteries)	120g (Not Including Batteries)	

Standard	Main Unit		
Accessories	Probe	5M Φ 8 Standard Probe	Built-in Probe
	Coupling Agent	✓	✓
	Carrying Case	B04	B04
	Operation Manual	✓	✓

Optional Accessories	Other Special-purpose Probes	
	RS-232C Data Cable with Software	
	Bluetooth Data Adapter with Software	

Probe Technical Parameters

Probe Model	Diagram	Measuring Range	Diameter	Frequency	Operating Temp.
5MHz $\Phi 8$ (UTG-ST) Standard Configure Probe		1.5 ~ 200 mm (Steel)	$\Phi 8 \text{ mm}$	5M Hz	0 ~ 50 °C
5MHz $\Phi 8$ (UTG-TP) Curved Surface Probe		1.5 ~ 200 mm (Steel)	$\Phi 8 \text{ mm}$	5M Hz	0 ~ 50 °C
2MHz $\Phi 10$ Plastics Measurement Probe		1.0 ~ 50 mm (Plastics)	$\Phi 10 \text{ mm}$	2M Hz	0 ~ 50 °C
2MHz $\Phi 10$ Cast Iron Measurement Probe		3.0 ~ 40 mm (Cast Iron)	$\Phi 10 \text{ mm}$	2M Hz	0 ~ 50 °C
5MHz $\Phi 6$ Thin Material Probe		1.0 ~ 50 mm (Steel)	$\Phi 6 \text{ mm}$	5M Hz	0 ~ 50 °C
5MHz $\Phi 12$ (UTG-HT) High Temperature Probe		3.0 ~ 200 mm (Steel)	$\Phi 12 \text{ mm}$	5M Hz	60 ~ 300 °C

BESTONE INDUSTRIAL LTD.

Tel: +86 755 82952326, Fax: +86 755 82952326

Web: www.bestone-meter.com

Email: liu@bestone-meter.com

Skype: Bestone-Shirley Liu

WhatsApp: +86 18929394326